



1 **EC TYPE-EXAMINATION CERTIFICATE**

2 Equipment intended for use in Potentially Explosive Atmospheres Directive 94/9/EC

3 Certificate Number: **Sira 08ATEX1293X** Issue: **0**

4 Equipment: **Centurion XP flameproof digital camera**

5 Applicant: **CorDEX Instruments Limited**

6 Address: Unit 6 Farfield
Main Road,
Wykeham
Scarborough
YO13 9QD
UK

7 This equipment and any acceptable variation thereto is specified in the schedule to this certificate and the documents therein referred to.

8 Sira Certification Service, notified body number 0518 in accordance with Article 9 of Directive 94/9/EC of 23 March 1994, certifies that this equipment has been found to comply with the Essential Health and Safety Requirements relating to the design and construction of equipment intended for use in potentially explosive atmospheres given in Annex II to the Directive.

The examination and test results are recorded in the confidential reports listed in Section 14.2.

9 Compliance with the Essential Health and Safety Requirements, with the exception of those listed in the schedule to this certificate, has been assured by compliance with the following documents:

EN 60079-0:2006 EN 60079-1:2007
IEC 60079-0:2007 was used as guidance in respect of marking

10 If the sign 'X' is placed after the certificate number, it indicates that the equipment is subject to special conditions for safe use specified in the schedule to this certificate.


11 This EC type-examination certificate relates only to the design and construction of the specified equipment. If applicable, further requirements of this Directive apply to the manufacture and supply of this equipment.

12 The marking of the equipment shall include the following:



II 2 G
Ex d IIC T4 Gb
Ta = -20°C to +50°C

Project Number 51A18791
C. Index 23


D R Stubbings BA MIET
Certification Manager

This certificate and its schedules may only be reproduced in its entirety and without change.

Sira Certification Service

Rake Lane, Eccleston, Chester, CH4 9JN, England

Tel: +44 (0) 1244 670900
Fax: +44 (0) 1244 681330
Email: info@siracertification.com
Web: www.siracertification.com



SCHEDULE

EC TYPE-EXAMINATION CERTIFICATE

Sira 08ATEX1293X
Issue 0

13 DESCRIPTION OF EQUIPMENT

The Centurion XP flameproof digital camera is basically a flameproof enclosure containing a digital camera. The device comprises a main enclosure with a bolt on external battery pack and a non-metallic overmoulding.

The main enclosure comprises of two main parts: the rear carriage and the front cover, the joint between these two parts forming a flanged flamepath. The rear carriage is secured to the front cover with ten M3 x 12 mm hexagonal socket cap head screws, the heads of these screws being protected by their location in appropriate counter bored holes.

The rear carriage includes a toughened glass viewing window as well as operating rods. Located to one side of the rear face of the rear carriage is a toughened glass window to allow the viewing of an internal LCD screen, the joint between the toughened glass window and the rear carriage forming a spigotted flamepath. The toughened glass window is secured by a retaining plate which is held in place by ten M3 x 6 mm hexagonal socket cap head screws, the heads of these screws being protected by their location behind the external overmoulding. To allow operation of the internal digital camera, the rear carriage is provided with six operating rods. The joint between the rods and the rear carriage forms a cylindrical flamepath. The operating rods are secured against displacement by an internal shoulder.

The front cover includes a further toughened glass window, a bolt on battery pack, a USB access port and additional operating rods. Located to one side of front face of the front cover is a toughened glass window to allow light to access the internal digital camera, the joint between the toughened glass window and the rear carriage forming a spigotted flamepath. The toughened glass window is secured by a retaining plate which is held in place by six M3 x 6 mm hexagonal socket cap head screws, the heads of these screws being protected by their location behind the external overmoulding. Located alongside the toughened glass window is a detachable battery pack. The battery pack comprises an aluminium housing containing two rechargeable AAA size batteries and associated circuitry. The joint between the battery pack and the front cover forms a flanged flamepath. The battery cover is secured by six M4 x 12 mm hexagonal socket cap head screws, the heads of these screws being protected by their location in appropriate counter bored holes. To allow operation of the internal digital camera, the front cover is provided with two operating rods. The joint between the rods and the front cover forms a cylindrical flamepath. The operating rods are secured against displacement by an internal shoulder. To allow access to the internal USB port the front cover is provided with a threaded access port. The port is provided with a M16 x 1.5 thread, the access port is sealed with an appropriate blanking element. Removal of the blanking element requires an Allen key.

All fasteners are stainless steel to ISO 4762, grade A2-70

The assembly is provided externally with a permanent, non-metallic, anti-static protective overmoulded case.



SCHEDULE

EC TYPE-EXAMINATION CERTIFICATE

**Sira 08ATEX1293X
Issue 0**

14 DESCRIPTIVE DOCUMENTS

14.1 Drawings

Refer to Certificate Annexe.

14.2 Associated Sira Reports and Certificate History

Issue	Date	Report number	Comment
0	17 June 2009	R51A18791A	The release of the prime certificate.

15 SPECIAL CONDITIONS FOR SAFE USE (denoted by X after the certificate number)

15.1 In accordance with clause 5.1 of EN 60079-1, the critical dimensions of the flamepaths are.

Flamepath	Maximum Gap (mm)	Minimum L (mm)
Rear carriage/front carriage	0.04	14.0
Front carriage/ battery pack	0.04	15.0
LCD Window/rear carriage	0.1	14.0
Lense window/front carriage	0.1	14.0
Operating rod/ rear and front carriage	0.1	10

15.2 This equipment must only be used where there is a low risk of mechanical impact. The equipment is manufactured in aluminium alloy, in Group I applications this equipment must not be utilised where there is a risk of thermite reaction frictional ignition.

16 ESSENTIAL HEALTH AND SAFETY REQUIREMENTS OF ANNEX II (EHSRs)

The relevant EHSRs that are not addressed by the standards listed in this certificate have been identified and individually assessed in the reports listed in Section 14.2.

17 CONDITIONS OF CERTIFICATION

17.1 The use of this certificate is subject to the Regulations Applicable to Holders of Sira Certificates.

17.2 Holders of EC type-examination certificates are required to comply with the production control requirements defined in Article 8 of directive 94/9/EC.