



"Your Direct Source for Plant Maintenance, Reliability, Test & Measurement"

www.reliabilitydirectstore.com

2911 South Shore Blvd. Suite 170, League City, TX USA 77573 Phone: 281-957-5283 Fax: 281-334-4255

Explosion-protected Inspection Lamp ISL 200 / 400-Ex

The ISL 200-Ex and the ISL 400-Ex are robust, cable-connected inspection lamps for industrial use in explosion-prone areas for zones I and 2I according to norm 1999/92/EG (ATEX 137). The inspection lamps are especially notable for their bright and extremely long-lasting illuminants.

The ISL 200-Ex and 400-Ex are especially suited to time-intensive maintenance and repair work. The units emit a uniform, bright light which greatly improves the working environment whilst helping to reduce fatigue in explosion-prone areas. The optional attachment clamps allow you to mount the lamp within reach at your office or workshop. You can also attach and orientate the ISL by utilising the integrated revolving hook or by using the optional magnetic fasteners.

The long-lasting cold cathode tubes are known primarily for their use in background lighting for flat screens, and have a very long lifetime. They surpass the longevity of traditional luminescent tubes by far. Since the tubes are also economical in terms of space, the ISL lamps provide more luminosity than ever in a compact, light and robust case.

The lamps are delivered with a 5 m cable end - which gives you the flexibility to connect the ex-plug of your choice.

The ISL 400 and ISL 200 set new standards in the field of repair and inspection lamps.



- Certified for use in zones I and 2I
 - Compact design thanks to a bright, long-lasting cold cathode light
 - Robust, impact-resistant IP 65 case
 - Available with 2 or 4 lamps
 - Available with optional protective basket
 - Rotating attachment hook
- Scope of delivery**
- ISL 200-Ex (2 cold cathode tubes)
 - ISL 400-Ex (4 cold cathode tubes)
 - 5 meter cable (attached), no plug
 - Instruction manual
- Optional accessories**
- Wall-mounting clips
 - Magnetic clips

Technical data:

Operating temperature:	-25°C...+55°C
Voltage range:	110V AC ... 254V AC 12, 24V AC 12, 24V DC

Lamps:	
(ISL 200-Ex)	2x CCFL
(ISL 400-Ex)	4x CCFL
Weight:	850g
Dimension:	approx. 595 mm x 60 mm
Protection rating:	IP 67

Ex-data:

Ex designation:
 Ⓜ II 2G Ex ed IIC T4
 Ⓜ II 2D IP65 Txx°C
 EC-Certificate of conformity:
 TÜV 06 ATEX 553464

Reliability Direct, Inc.

Visit our e-commerce stores for plant maintenance and reliability:
www.reliabilitydirectstore.com, www.extech-direct.com