



"Your Direct source for Plant reliability. Maintenance. Test & Measurement"

www.reliabilitydirectstore.com

2911 South Shore Blvd. Suite 170, League City, TX USA 77573 Phone: 281-291-957-5283 Fax: 281-334-4255




FLIR i-Series

NEW!

Thermal Imaging InfraRed Cameras

High Resolution Visible Light Cameras with Fusion (PIP)




Fusion - Picture in Picture



Built-in Laser Pointer



Built-in Illuminator Lights




Thumbnail Image Gallery



i-Series Features

- Latest Infrared Detector Technology
- Fusion Picture in Picture (PIP)
- Bright LED Lamp for Quality Visible Images
- Thermal Sensitivity of $<0.1^{\circ}\text{C}$ @ 25°C
- Lightweight — Weighs only 1.3lbs
- Easy One-handed Operation
- 3.5" LCD with Razor Sharp Resolution
- Convenient Thumbnail Image Gallery

- Visible Light Digital Camera — Up to 2.3MP resolution with LED lamps provides sharp images regardless of lighting conditions
- Fusion Picture in Picture (PIP) — Displays thermal image super-imposed over a digital image
- 0.1°C Thermal Sensitivity — Provides the resolution needed to find problems faster and easier
- Wide Temperature Range — Measures from -4 to 662°F (-20 to 350°C) targeting electrical and industrial applications
- Thumbnail Image Gallery — Allows quick search of stored images
- Laser LocatIR™ Pointer — Pinpoints the hot spot on the IR image with the real physical target (FLIR i50 and i60 only)
- Radiometric JPEG Images — Patented technology used to save images in standard JPEG format for easy emailing and analysis using QuickReport™ PC Software (included)
- 1GB microSD Card — Stores more than 1000 Radiometric JPEG images
- Li-Ion Rechargeable Battery — Replaceable battery lasts for 5hrs of continuous use
- Area (Min/Max) Mode — Spot marker shows the Minimum or the Maximum Temperature reading within the selected area
- Includes — 1GB micro SD Card, miniSD adaptor, Li-Ion rechargeable battery, power supply, QuickReport™ software, USB cable, lens cap, hand strap, and heavy duty case
- FLIR i40 Additional Features
 - 0.6MP Visible Light: Camera resolution
 - Picture in Picture (PIP) fixed
 - 14,400 pixels (120 x 120)
- FLIR i50 Additional Features
 - 2.3MP Visible Light: Camera resolution
 - Picture in Picture (PIP) with 3 fixed steps
 - 19,600 pixels (140 x 140)
 - Built-in Laser LocatIR™ pointer
- FLIR i60 Additional Features
 - 2.3MP Visible Light: Camera resolution
 - Scalable Picture in Picture (PIP) feature (see right illustration)
 - 32,400 pixels (180 x 180)
 - Built-in Laser LocatIR™ pointer
 - Laser Marker Function
 - Auto Hot/Cold spot marker function shows a spot within the area that automatically finds the hottest or coldest spot within the box




FLIR i60 — Scalable Fusion picture in picture feature permits you to resize the thermal image as needed on a large 3.5" color display



The Difference is Training

Get the most out of your FLIR IR camera investment with world-class instruction through the Infrared Training Center (ITC), the largest infrared applications training organization in the world. The ITC's Level 1 Infrared Thermography Training Course is geared to the new infrared camera user and focuses on its use for a variety of condition monitoring/predictive maintenance applications. Level 2 and Level 3 certificate courses for more advanced infrared training are also available. Courses are taught by certified instructors with extensive experience in a wide variety of infrared thermography and thermal imaging applications. ITC certifications are recognized by major professional organizations.




QuickReport™ PC software enables user to analyze temperature of all thermal pixels of any FLIR Camera JPEG images




Applications




Motor: Bearing Problem



Motor: Internal Winding Problem



Electric: Hot Fuses



Building: Heat Loss



FLIR i-Series Specifications

Features	FLIR i40	FLIR i50	FLIR i60
Temperature range	-4°F to 662°F (-20°C to 350°C)	-4°F to 662°F (-20°C to 350°C)	-4°F to 662°F (-20°C to 350°C)
Temperature accuracy	±2°C or ±2% of reading	±2°C or ±2% of reading	±2°C or ±2% of reading
Image Storage (168 micro SD card)	1000 Images	1000 Images	1000 Images
Emissivity Table	0.1 to 1.0 (adjustable)	0.1 to 1.0 (adjustable)	0.1 to 1.0 (adjustable)

Imaging Performance / Image Presentation			
Field of view/mir focus distance	25° X 25°/0.10m (3.9")	25° X 25°/0.10m (3.9")	25° X 25°/0.10m (3.9")
Thermal sensitivity (N.E.T.D.)	<0.1°C at 25°C	<0.1°C at 25°C	<0.1°C at 25°C
Detector Type - Focal plane array (FFA) uncooled microbolometer	14,400 pixels (120 X 120)	19,600 pixels (140 X 140)	32,400 pixels (180 X 180)
Spectral range	7.5 to 13µm	7.5 to 13µm	7.5 to 13µm
Display	3.5" color LCD	3.5" color LCD	3.5" color LCD
Video output	MPEG 4 via USB	MPEG 4 via USB	MPEG 4 via USB
Image Modes	Thermal, Visual, Fusion	Thermal, Visual, Fusion	Thermal, Visual, Fusion
Fusion Picture in Picture (PIP)	Fixed	3 fixed steps	Scalable
Visible Light Camera Resolution	0.6 Megapixels	2.3 Megapixels	2.3 Megapixels
Laser / Classification	—	Yes / Class 2	Yes / Class 2
Laser Type	—	Semiconductor AlGaInP Diode Laser: 1mW/635nm	Semiconductor AlGaInP Diode Laser: 1mW/635nm
Laser Marker Function	—	—	On IR image
Spot (center Measurement mode)	Yes	Yes	Yes
Auto Hot/Cold Spot Marker	—	—	Yes
Area (min/max) Measurement mode	Yes	Yes	Yes
Image Controls (All models)	Palettes (Iron, Rainbow and Black/White), level, span, auto adjust (continuous/manual)	Palettes (Iron, Rainbow and Black/White), level, span, auto adjust (continuous/manual)	Palettes (Iron, Rainbow and Black/White), level, span, auto adjust (continuous/manual)
Focus	Manual	Manual	Manual
Set-up controls (All models)	Date/time, info, LCD intensity, power down, and 21 languages	Date/time, info, LCD intensity, power down, and 21 languages	Date/time, info, LCD intensity, power down, and 21 languages
Battery Type/operating time	Li-Ion/ 5 hours, Display shows battery status	Li-Ion/ 5 hours, Display shows battery status	Li-Ion/ 5 hours, Display shows battery status
Dimensions/Weight	9.3x3.2x6.9" (235x81x175mm)/~1.32lbs (600g), including battery	9.3x3.2x6.9" (235x81x175mm)/~1.32lbs (600g), including battery	9.3x3.2x6.9" (235x81x175mm)/~1.32lbs (600g), including battery

EXTECH Ordering Information

Part Number	Product Description	Price
FLIR i40	Thermal imaging InfraRed Camera	\$4995.00
FLIR i50	Thermal imaging InfraRed Camera with Laser	\$5995.00
FLIR i60	Thermal imaging InfraRed Camera with Laser and scalable PIP	\$7995.00
ACCESSORIES		
1196398	Li-Ion Rechargeable Battery	\$199.00
1910389	AC Adapter Charger (110-240V, U.S. Plug)	\$300.00
1910490	Cigarette Lighter Adapter Kit, 12VDC (1.2m cable)	\$99.00
1196474	2-Bay Battery Charger including Power Supply (U.S. plug)	\$450.00
1122000	Camera Pouch Case	\$175.00
CERTIFICATION TRAINING		
ITC LEVEL 1	ITC Level 1 Certification Training per attendee	\$1750.00

RELIABILITY DIRECT, INC.

2911 S. Shore Blvd., Suite 170 League City, TX USA 77573 Tel: 281.957.5283 Fax: 281.334.4255