



"Your One Stop Shop for Condition Monitoring"

www.reliabilitydirectstore.com

2911 South Shore Blvd. Suite 170, League City, TX USA 77573 Phone: 281-334-0766 Fax: 281-334-4255

Intrinsically Safe LED pocket Flashlight Lite-Ex LED 30



The Lite-Ex LED 30 is a compact, robust and easily operated LED-Flashlight, certified to NEC 500 and ATEX regulations to be used in hazardous (classified) locations.

- Operates for 80 hours
- Robust metal housing
- 3-LED's with reflectors
- LED life expectancy up to 100,000 operating hours
- Certified for use in Dust Ex-Zones 22 and 21 (ATEX)



Compact and easy to handle, the Lite-Ex LED 30 is ideal for inspection lighting in hazardous (classified) locations.

Ex-data:
 Ex-designation:
 Ⓜ II 1 G EEx ia IIC T4
 Ⓜ II 2 D T90°C IP 52
 EC-Certificate of conformity:
 ZELM 02 ATEX 0104

 I.S. Class I Division 1 Group A-DT4

Accessories:
 Spare battery type N

Technical Data:
 Ambient temperature Ta: -4°F to 122°F (-20°C ... +50°C)
 Storage temperature: -4°F to 140°F (-20°C ... +60°C)
 Operating time: 80 hours
 Power supply: 3 x type N battery (type proofed batteries)
 Weight: approx. 5.5 oz (with batteries)
 Dimensions: 5.5" x 1" (L x ø)
 140 x 26 mm (L x ø)