

SKF HMVC 170E

Hydraulic nut for mounting or dismounting of bearings, with inch thread



Facilitates easy and quick application of the high drive-up forces required for mounting bearings on tapered seatings. The hydraulic nut can also be used for dismounting bearings mounted on either adapter or withdrawal sleeves.

- Quick connection coupling can be fitted on the face or side of the nut
- A spare set of piston seals and maintenance kit is included
- Supplied with a quick connection coupling to fit the SKF hydraulic pumps
- Equipped with eyebolts, two tommy bars and four mating holes on their front face

Dimensions

Connecting thread	33.473 - 3
Thread form	ACME General Purpose Threads Class 3 G
Thread pitch diameter	33.2874 in
Maximum piston displacement	1.0236 in
Outer diameter	40.1575 in
Piston area	178 in ²
Piston inner diameter	33.5433 in
Piston outer diameter	38.9764 in
Piston width	0.6299 in
Width	3.2677 in

Performance

Maximum pressure	3626 psi
Maximum pressure (MPa)	25 MPa

Properties

Type	Imperial thread
------	-----------------

Logistics

Country of Manufacturing (COM code)	18 - Germany
Product net weight	443 lb

eClass code	23-05-19-01
UNSPSC code	73152101

Compatible products

Type	Designation	Description	Qty
Spare part	729832 A	Quick connecting nipple	1
Spare part	HMV 170/233983	Spare O-ring set for Hydraulic nut (all versions)	1
Spare part	HMVE M5X17	Spare nylon screw for Hydraulic nuts for size 70 and larger, 10 pcs	1
Spare part	HMVM 70/200	Spare maintenance set for Hydraulic nuts, size 70 to 200	1
Accessory	729865 A	Feeler gauge	1
Accessory	729865 B	Feeler gauge	1
Accessory	TMCD 1/2R	Horizontal dial gauge for Hydraulic nuts	1
Accessory	TMCD 10R	Horizontal dial gauge for Hydraulic nuts	1
Accessory	TMCD 5P	Vertical dial gauge for Hydraulic nuts	1
Recommended product	TMJL 50DU	Hydraulic Pump for the SKF Drive-up Method for larger size Hydraulic nuts	1
Recommended product	TMJL 50	Hydraulic pump with large oil container	1
Recommended product	728619 E	Hydraulic pump with large oil container	1