

SKF LGMT 3/18

General purpose industrial and automotive bearing grease



A mineral oil based, lithium soap thickened grease. This premium quality, general purpose grease is suitable for a wide range of industrial and automotive applications requiring stiff grease.

- Excellent rust inhibiting properties
- High oxidation stability within its recommended temperature range

Performance

Suitable for High load applications	■■■■■
Suitable for Vertical shaft applications	■■■■■
Suitable for applications with Oscilating movements	■■■■■
Suitable for applications with Severe vibrations	■■■■■
Suitable for applications that require Rust protection	■■■■■
Suitable for applications that require Water resistance	■■■■■
Suitable for applications that require Frequent start-up	■■■■■
Operating temperature range	-22 – 248 °F
Load Range	Low - Medium C/P > 8
Speed Range	Medium
Dropping point (min) ISO 2176	356 °F
Penetration DIN ISO 2137, Worked, 60 strokes (10 ⁻¹ mm)	220 - 250
Penetration DIN ISO 2137, Prolonged (max.), 100 000 strokes, 10 ⁻¹ mm	280
Mechanical stability - Roll stability, ASTM D1831 (max.) 50 hrs at 80°C, 10 ⁻¹ mm	295
Mechanical stability, V2F test, 144 hrs	M
Corrosion protection, Emcor, ISO 11007, Distilled water	0-0
Corrosion protection, Emcor, ISO 11007 modified, Water washout	0-0
Corrosion protection, Emcor, ISO 11007 modified, 0.5% NaCl	-

Water resistance (max.) DIN 51807/1, 3 hrs at 90 °C	1
Oil separation DIN 51817, 40°C, %	1-3
Lubrication ability, R2F test B at 120°C	Pass
Copper corrosion (max.) DIN 51811 /ASTM D4048, 24 hrs at 100°C	2 max.at 130°C
Rolling bearing grease life (max.) ROF test, L50 life, 10000 r/min, hrs at °C	1000 at 130°C

Properties

Category	Bearing grease
Lubricant	LGMT 3
NLGI consistency class	3
Base oil viscosity DIN 51562 at 40 °C	125 mm²/s
Base oil viscosity DIN 51562 at 100 °C	12 mm²/s
Biodegradable	No
Food Grade	No
DIN 51825 code	K3K-30
Thickener	Lithium
Colour	Amber
Base oil type	Mineral
Shelf life	5 year
Available for single point lubrication	yes

Logistics

Country of Manufacturing (COM code)	17 - Belgium
Product net weight	39.7 lb
eClass code	23-06-01-01
UNSPSC code	15121902

Compatible products

Type	Designation	Description	Qty
Recommended product	LGMT 3/0.4	General purpose industrial and automotive bearing grease	1
Recommended product	LGMT 3/0.5	General purpose industrial and automotive bearing grease	1
Recommended product	LGMT 3/1	General purpose industrial and automotive bearing grease	1
Recommended product	LGMT 3/180	General purpose industrial and automotive bearing grease	1
Recommended product	LGMT 3/5	General purpose industrial and automotive bearing grease	1

Type	Designation	Description	Qty
Recommended product	LGMT 3/50	General purpose industrial and automotive bearing grease	1
Recommended tool	LAGG 18M	Grease pump for use on drums	1
Recommended tool	TMBA G11DB	Lubrication tool accessories	1
Recommended tool	LAGG 18AF	Air-driven grease pump for use on grease drums/ pails, mobile	1
Recommended tool	LAGT 18-50F	Grease trolley for grease drums/ pails, for Air-driven grease pumps	1
Recommended tool	LAGG 18AE	Air-driven grease pump for use on grease drums/ pails, mobile	1